



Device Material Content

5555 NE Moore Ct.
Hillsboro OR 97124
custreq@latticesemi.com

November, 2020

Package: 237 ftBGA
Total Device Weight 0.814 Grams

Package Code:

FTG237

Products:

LPTM21

Assembly: ASEM

Size (mm): 17 x 17

Lead pitch (mm): 1.0

MSL: 3

Reflow max (°C): 260

	% of Total Pkg. Wt.	Weight (g)	% of Total Pkg. Wt.	Weight (g)	Substance	CAS #	% of Subst.	Notes / Assumptions:
Die	1.06%	0.0086	1.06%	0.0086	Silicon chip	7440-21-3	100.00%	Die 1: 2.58 x 2.52 mm Die 2: 2.89 x 2.89 mm Side-by-side (dual-die)
Mold Compound	49.90%	0.4062	2.50%	0.0203	Epoxy Resin A	-	5.00%	Mold compound: Sumitomo EME-G750E
			0.85%	0.0069	Epoxy Resin B	-	1.70%	
			2.50%	0.0203	Phenol Novolac	9003-35-4	5.00%	
			41.42%	0.3371	Silica Fused	60676-86-0	83.00%	
			2.50%	0.0203	Metal Hydroxide	-	5.00%	
			0.15%	0.0012	Carbon Black	1333-86-4	0.30%	
D/A Epoxy	0.15%	0.0012	0.12%	0.00098	Silver	7440-22-4	80.00%	Die attach epoxy: Henkel (Ablebond) 2100A
			0.03%	0.00024	Esters & resins	-	20.00%	
Wire	0.38%	0.0031	0.38%	0.00307	Gold (Au)	7440-57-5	99.00%	Pd coated Au, 0.8 mil diameter; 1 wire per solder ball
			0.00%	0.00003	Palladium	7440-05-3	1.00%	
Solder Balls	14.14%	0.1151	13.65%	0.1111	Tin (Sn)	7440-31-5	96.50%	SAC305
			0.42%	0.0035	Silver (Ag)	7440-22-4	3.00%	
			0.07%	0.0006	Copper (Cu)	7440-50-8	0.50%	
Substrate	23.87%	0.1943	7.64%	0.0622	BT Resins	-	32.00%	BT Resin CCL-HL832NX-A
			16.23%	0.1321	Glass fiber	65997-17-3	68.00%	
Foil	4.77%	0.0389	2.86%	0.0233	Copper	7440-50-8	59.97%	
			1.81%	0.0148	Nickel plating	7440-02-0	38.01%	
			0.10%	0.0008	Gold plating	7440-57-5	2.02%	
Solder Mask	5.73%	0.0466	3.22%	0.0262	Quartz	14808-60-7	56.20%	Solder mask PSR4000 AUS 308
			0.92%	0.0075	3-methoxy-3-methylbutylacetate	103429-90-9	16.00%	
			1.26%	0.0103	Barium Sulfate	7727-43-7	22.00%	
			0.17%	0.0014	Talc	14807-96-6	3.00%	
			0.03%	0.0002	Naphthalene	91-20-3	0.50%	
			0.13%	0.0011	Trade secret ingredients	-	2.30%	

Lattice regards this materials information to be correct but makes no guarantee as to its accuracy or completeness, including, but not limited to, with respect to its compliance with applicable environmental laws and regulations. Lattice subcontractors the production, test and assembly of hardware devices to independent third-party vendors and materials suppliers ("Contractors"). All data provided hereunder is based on information received from Contractors. Lattice has not independently verified the accuracy or completeness of this information which is provided solely for your reference in connection with the use of Lattice products.

www.latticesemi.com



Rev. J