

Device Material Content

5555 NE Moore Ct. Hillsboro OR 97124

Package: 28 PDIP with SnPb Plating

(503) 268-8000 Total Device Weight 2.00 Grams

August, 2008	% of Total Pkg. Wt.	Weight (g)	% of Total Pkg. Wt.	Weight (g)	Substance	CAS#	Notes / Assumptions:
Die	0.52%	0.010			Silicon chip	7440-21-3	Die size: 3.3 x 2.7 x 0.50 mm
Mold	72.81%	1.456	62.40% 4.37% 4.37% 1.46% 0.22%	1.248 0.087 0.087 0.029 0.004	Silica Fused Epoxy Resin Phenol Resin Epoxy, Cresol Novolac Carbon black	- - 29690-82-2	Mold Compound Density between 1.7 and 1.9 grams/cc 75 to 95% Silica Fused (LSC uses 85.7% in our calculation) 2 to 8% Epoxy Resin (LSC uses 6% in our calculation). 2 to 8% Phenol Resin (LSC uses 6% in our calculation) 1 to 3% Cresol Novolac Epoxy (LSC uses 2% in our calculation). 0.1 to 0.5% Carbon black (LSC uses 0.3% in our calculation)
D/A Epoxy	0.05%	0.0009	0.04% 0.01%	0.0007 0.0002	Silver-filled epoxy Silver (Ag) other	7440-22-4	Die attach epoxy Density: 4 grams/cc (silver content: 60-100%; LSC uses 80% in our calculation)
Wire	0.06%	0.0010			Gold (Au)	7440-57-5	1.2 mil wire diameter; 1 wire for each package lead; wire length 3 mm
Lead Plating	2.07%	0.041	1.76% 0.31%	0.0351 0.0062	Tin (Sn) Lead (Pb)	7440-31-5 7439-92-1	Nominal: 85% Sn, 15% Pb Thickness is 0.015mm
Leadframe	24.49%	0.490	23.87% 0.58% 0.03% 0.02%	0.477 0.012 0.0006 0.0003	Copper (Cu) Iron (Fe) Zinc (Zn) Phosphorus (P)	7440-50-8 7439-89-6 7440-66-6 7723-14-0	Leadframe thickness is nominal (per Case Outline). 97.46% Cu 2.35% Fe 0.12% Zn 0.07% P

Notes

The values listed above are nominal values based on studies of representatives of this particular package type, and are believed to be as accurate as possible.

Constituent substances and proportions in epoxy materials are before curing.

The information provided above is representative of the package as of the date listed, and is subject to change at any time.

www.latticesemi.com